



**SAFE**TRANSFER®



**SAFE**  
TRANSFER®

OFFSHORE  
PERSONNEL  
BASKET

[www.safetransfer.dk](http://www.safetransfer.dk)

**SAFETRANSFER®**

## Offshore personnel basket from West-Marine



**4-PERSONS**



**8-PERSONS**



## Facts

# Certificates and Specifications

### SAFE TRANSFER® CERTIFICATES

- DNV GL - Type Approval Certificate  
Standard for Certification 2.22 Lifting Appliances
- Danish Technological Institute (Notified Body)
- European Standard EN 14502-1:2010  
Cranes-Equipment for lifting of persons Part 1. suspended baskets
- NDT and load test
- Certified chain lifting sling

#### SPECIFICATIONS, 4-PERSONS

- Width: 2.600 mm
- Height: 3.222 mm
- Weight: 465 kg
- Capacity: 4 persons
- Max. load (payload): 500 kg

#### SPECIFICATIONS FOR TRANSPORT WITHOUT BOTTOM FENDER MOUNTED

- Width: 2118 mm
- Length: 3380 mm
- Height: 2349 mm
- Weight incl. sling and cover: 520 kg

#### SPECIFICATIONS, 8-PERSONS

- Width: 2.600 mm
- Height: 3.340 mm
- Weight: 510 kg
- Capacity: 8 persons
- Max. load (payload): 1.000 kg

#### SPECIFICATIONS FOR TRANSPORT WITHOUT BOTTOM FENDER MOUNTED

- Width: 2118 mm
- Length: 3427 mm
- Height: 2392 mm
- Weight incl. sling and cover: 570 kg

## Emergencies

Provides safe transfer  
of injured personnel



#### STRAP TIGHTENERS

Strap tighteners are used for securing stretcher to the basket.

# Key features

## RIGID FRAME IN CORROSION RESISTANT STAINLESS STEEL AISI 316L



### WELDING

All weldings are performed by certified welders and in accordance with procedures approved by DNV GL. All primary structure weldings are fully penetrant tested.



### NON-SKID FLOORING

All entrances/exits are fitted with non-skid flooring to ensure safe entrance and exit.



### VERTICAL RIGID STRUCTURE

The vertical rigid (stainless steel) parts of the SAFE TRANSFER® baskets are covered with synthetic foam for protection.



### SHOCK ABSORBING FUNCTION

Large floats and bottom fenders are fitted underneath the basket deck to provide shock-absorbing function for softer landing.



### LIFTING SLING

SAFE TRANSFER® are delivered with a chain lifting sling fitted with a compensator in a highly visible material. The compensator serves as a tag line, helping to control the basket by the crane operator. Length of chain: 2,30 mtr. Total length: 3 mtr.



### NETS

Four rope webbings, made of spliced rope, are attached to the upper and lower stainless steel structure. The rope webbings provide added security for personnel inside the basket.



### BOTTOM DECK

A heavy aluminium plate with anti-slip pattern is used as bottom deck.



### CLOSING STRAPS

Rope webbings are fitted with fast clickbuckle straps ensuring fast and easy exit.



## **SAFE**TRANSFER®

The safe personnel transfer basket from West-Marine.

SAFE TRANSFER® enables safe, quick and effective transfer between offshore installations, drilling rigs and vessels.

The basket is constructed to considerably enhance safety and confidence levels for personnel during transfers. West-Marine SAFE TRANSFER® is certified by DNV GL.

SAFE TRANSFER® is produced in the EU.



# West-Marine A/S

The right solutions  
since 1969

SAFE TRANSFER® is a 100% owned subsidiary  
of WEST-MARINE A/S.

WEST-MARINE A/S has worked in the maritime  
industry since 1969 both as service provider and  
exclusive partner for different agencies/products.  
All products are focusing on the maritime segment  
providing high quality and safety as keywords.

The SAFE TRANSFER® personnel basket was originally  
developed by one of the owners of WEST-MARINE A/S  
more than 20 years ago and continuously  
enhanced ever since.

Please visit our website ([www.west-marine.dk](http://www.west-marine.dk))  
for more information.



## **WEST-MARINE A/S**

Fiskerihavnsgade 30 - 32, DK-6700 Esbjerg

Phone +45 75 45 70 44, Fax +45 75 13 21 48

E-mail: [info@west-marine.dk](mailto:info@west-marine.dk)

[www.west-marine.dk](http://www.west-marine.dk)